

Product Code: OA411AGU

Description: 10AX 1 Gang 2 Way IP66 Weatherproof Switch Unit



General Information

Dimensions	91mm (W) x 106mm (H) x 72.5mm (D)	
External Finish	Anthracite Grey	
Materials	Cover, Housing & Clip: Polycarbonate Switch Membrane: Neoprene Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Seal & Gasket: Rubber Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
Maximum Voltage	250V~ 50Hz	
Load Rating	10AX (Suitable for Inductive Loads)	
Terminal Size	3.5mmø	
Terminal Torque	0.5Nm	
Terminal Capacity	4 x 1.5mm ² or 2 x 2.5mm ²	
Two Way	Yes	
Ingress Protection	IP66	
Termination Type	Screw	
Back Box Knockouts	5 x 20mmø	
Operational Temperature	-5°C to +40°C	
Warranty	5 Years	
Standards	BS EN 60669-1:1999 +A1:2002 +A2:2008 BS EN 60529: 2011 (Sections 13 & 14)	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.
Interchangeable with 13A/10AX modules in the MiniGrid Range. 