

**Product Code:** OA412AGU

**Description:** 10AX 2 Gang 2 Way IP66 Weatherproof Switch Unit



### General Information

<b>Dimensions</b>	91mm (W) x 106mm (H) x 72.5mm (D)	
<b>External Finish</b>	Anthracite Grey	
<b>Materials</b>	Cover, Housing & Clip: Polycarbonate Switch Membrane: Neoprene Rear Housing: Nylon Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass	Seal & Gasket: Rubber Switch: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass
<b>Maximum Voltage</b>	250V~ 50Hz	
<b>Load Rating</b>	10AX (Suitable for Inductive Loads)	
<b>Terminal Size</b>	3.5mmø	
<b>Terminal Torque</b>	0.5Nm	
<b>Terminal Capacity</b>	4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>	
<b>Two Way</b>	Yes	
<b>Ingress Protection</b>	IP66	
<b>Termination Type</b>	Screw	
<b>Back Box Knockouts</b>	5 x 20mmø	
<b>Operational Temperature</b>	-5°C to +40°C	
<b>Warranty</b>	5 Years	
<b>Standards</b>	BS EN 60669-1:1999 +A1:2002 +A2:2008 BS EN 60529: 2011 (Sections 13 & 14)	

### Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
Interchangeable with 13A/10AX modules in the MiniGrid Range. 