

Product Code: OA652T

Description: 13A Fused Connection DP Switched IP66 Weatherproof Unit With Neon
(Semi-Transparent Lid)



General Information

Dimensions	87mm (W) x 158mm (H) x 90mm (D)	
External Finish	Anthracite Grey With Semi-Transparent Cover	
FCU Finish	Anthracite Grey With White Switch	
Materials	Cover, Housing & Clip: Polycarbonate Accessory Plate & Housing: Urea Terminals: Brass Contacts: Silver "on-lay" Copper / Brass Earth Strap: Mild Steel	Seal & Gasket: Rubber Neon Lens: Polycarbonate Terminal Screws: Steel & Yellow Passivated Internal Busbars: Formed Pressed Brass
Maximum Voltage	250V~ 50Hz	
Load Rating	13A	
Accessory Fixing Centres	60.3mm	
Terminal Size	5mmø	
Terminal Torque	2.0Nm	
Terminal Capacity	3 x 2.5mm² or 2 x 4mm²	
Lockable Cover	Yes (Lock Not Supplied)	
Double Pole	Yes	
Twin Earth Terminals	Yes	
Neon Indicator	Yes (Orange)	
Fuse Fitted	Fused	
Ingress Protection	IP66	
Termination Type	Screw	
Back Box Knockouts	7 x 20mmØ	
Operational Temperature	-5°C to +40°C	
Warranty	5 Years	
Standards	BS 1363-4: 2016 +A1: 2018 BS 1362:1973 BS EN 60529:1992+A2:2013 (Sections 13 & 14)	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All grey & white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.